RH Series Single-Mast Cargo Lift

Material Lifts | Model: RH-SERIES-SINGLE-MAST-CARGO-LIFT

STANDARD COMPONENTS

Caged platform, single 10# channel steel mast, carriage with 77-type bearings, electric wire-rope drive or hydraulic power pack, 500 kg anti-fall device, control, anchor fixings.

TECHNICAL SPECIFICATIONS

Drive: electric wire-rope traction (RH-E) or hydraulic (RH-H)
Lifting height: 2-10 m, 1 m increments
Rated load: 330 kg (2-8 m electric), 790 kg (9-10 m electric), 1,000 kg (hydraulic)
Safety load: 400 kg; 500 kg type anti-fall device fitted
Platform: 1,000 × 1,000 mm standard, custom up to 1,000 × 1,500 mm
Guide rail: 10# channel steel, approx. 5 mm wall thickness
Bearings: 77-type special bearings on the carriage
Wire rope: 6 mm oiled steel rope (electric models)
Power supply: 220 V single phase; 1,600 W (2-8 m) / 3,000 W (9-10 m)
Mast height: lifting height + 1.4 m (electric), + 1.0 m (hydraulic)
Protection: full-height cage guard rails
Working temperature: 0-50 degrees C
Colours: white / light grey / dark grey / black / blue / yellow
Certification: ISO 9001; CE at company level — confirm the documentation for your market
Warranty: 12 months
MOQ: 1 unit